



Product Name: Dura-Kote WB White Tint Base Epoxy (A)
Revision Date 10/01/13

MATERIAL SAFETY DATA SHEET

SECTION 1 Product and Company Identification

Product

Product Name: Dura-Kote WB White Tint Base Epoxy (part "A")
Product Description: Finishing aid
Intended Use: Cementitious sealer

Company

Manufacturer: SureCrete Design Products, Inc.
15246 Citrus Country Drive
Dade City, FL 33523
USA

Contact: 352-567-7973 (telephone general)
800-424-9300 (telephone emergency – Chemtrec)
813-469-1408 (telephone 24 hour emergency)
813-469-1419 (telephone 24 hour emergency)
info@surecretedesign.com (e-mail)
352-521-0973 (facsimile)

SECTION 2 Hazards Identification

Most Important Hazards

WARNING!

Harmful in contact with skin or swallowed. Inhalation causes headaches, dizziness, drowsiness, and nausea; and may lead to unconsciousness. Causes eye irritation. May cause respiratory tract and skin irritation.

SECTION 3 Composition / Information on Ingredients

This material is regulated as a mixture

Ingredient	CAS #	EC#	% (by weight)
Hazardous			
Aliphatic polyamine	proprietary	proprietary	<30%
2- Propoxyethanol	2807-30-9	220-548-6	<10%
Glacial Acetic Acid	64-19-7	NE	<5%
Non Hazardous			
Kaolin Clay	1332-58-7	310-194-1	<5%
Nepheline Syenate	37244-96-5		<5%
Water			<60%

or

Ingredient	CAS #	EC#	% (by weight)
Hazardous			
Aliphatic polyamine	proprietary	proprietary	<25%
2- Propoxyethanol	2807-30-9	220-548-6	<10%
Glacial Acetic Acid	64-19-7	NE	<15%
Titanium Dioxide	13463-67-7	NE	<30%
Non Hazardous			
Kaolin Clay	1332-58-7	310-194-1	<5%



Product Name: Dura-Kote WB White Tint Base Epoxy (A)
Revision Date 10/01/13

Nepheline Syenate	37244-96-5		<5%
Water			<40%

SECTION 4 First Aid Measures

Eye Contact: Rinse with running water for 15 mins. Hold eyelids apart while irrigating. Get medical attention.

Skin Contact: Flush contaminated skin with plenty of water. Remove contaminated clothing. Chemical burns must be treated promptly by a physician.

Inhalation: Move to fresh air. Administer artificial respiration if not breathing. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion: Get medical attention immediately. Do not induce vomiting.

SECTION 5 Fire Fighting Measures

Extinguishing Media:

Appropriate: Use an extinguishing agent suitable for the surrounding fire

Inappropriate: None known

Fire Fighting Procedures: Cool containers to prevent pressure buildup and possible explosion when exposed to extreme heat. Full protective equipment, including self-contained breathing apparatus required.

Unusual Fire and Explosion Hazard: Closed containers can explode due to buildup of pressure when exposed to extreme heat.

Hazardous Combustion Products: Oxides of carbon

Flammability Properties

Flash Point (Method): not determined

Flammable Limits (Approximate volume % in air): not determined

Autoignition Temperature: not determined

SECTION 6 Accidental Release Measures

Personal precautions: Evacuate personnel to safe areas. Ventilate area. Do not touch or walk through spilled material.

Environmental precautions: Prevent entry into waterways and soil.

Methods for clean-up: Small spills may be diluted with water and mopped up, or absorbed with paper toweling and disposed into approved container. Larger spills absorb onto sand, vermiculite, or any other inert, non-combustible material. Scoop into containers for later appropriate disposal.

SECTION 7 Handling and Storage

Handling: Avoid contact with eyes, skin, and clothing. Avoid handling of vapor or mist. Do not permit eating, drinking, smoking near material.



Product Name: Dura-Kote WB White Tint Base Epoxy (A)
Revision Date 10/01/13

Storage: Keep containers tightly closed, in dry, cool, well ventilated place. Keep out of reach of children.

SECTION 8 Exposure Control / Personal Protection

Exposure limit values: Consult local authorities for acceptable exposure limits. Known limits for some components are not applicable, as this compound is in an aqueous state.

Occupational exposure controls: Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

Respiratory protection: Wear suitable NIOSH approved respirator when ventilation is inadequate

Hand protection: Chemically compatible gloves

Eye protection: Safety glasses with side shields

Skin protection: Minimize skin contact with appropriate long-sleeved clothing

Hygiene measures: Observe good industrial hygienic practices. Frequently launder or discard proactive clothing, equipment.

Environmental exposure controls: Emissions from work process equipment should be checked against requirements of appropriate environmental protection legislation. In some cases alteration to work process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9 Physical and Chemical Properties

General

Physical state: liquid

Color: milky faint yellow

Odor: amine

Safety Data

pH: not available

Boiling point: 100-150°C / 212-302°F

Flash point: >93°C / 200°F

Flammable limits (approximate volume % in air): no data available

Vapor pressure (mm Hg.): <27 mm/Hg @ 20°C / 68°F

Water solubility: miscible

Vapor density (air = 1): >1

Density: 1080 kg/m³ @ 20°C / 68°F

SECTION 10 Stability and Reactivity

Stability: Stable under normal conditions

Conditions to avoid: Exposure to sources of ignition. Extreme temperature and direct sunlight.

Materials to avoid: Strong acids and bases

Hazardous decomposition products: Hazardous decomposition will not occur under normal conditions.

Hazardous polymerization: will not occur under normal conditions



Product Name: Dura-Kote WB White Tint Base Epoxy (A)
Revision Date 10/01/13

SECTION 11 Toxicological Information

Acute Toxicity

Route of Exposure	Conclusion / Remarks
<i>Inhalation</i>	
Toxicity : LC50 1530 ppm/7 hr.	
Irritation: data available	Elevated temperatures or mechanical action may form vapors, mist, or fumes that may be irritating to the eyes, nose, throat, or lungs based on available literature
<i>Ingestion</i>	
Toxicity: LD50 3,086 mg/kg (rat)	Low toxicity
<i>Skin</i>	
Toxicity: LD50 870 mg/kg (rabbit)	Low toxicity
Irritation: data available	Not irritating to the skin based on available literature
<i>Eye</i>	
Irritation: data available	Moderately irritating to the eyes based on available literature

Chronic / Other Effects

There are no recognizable hazards for human beings, if used as intended.

Titanium Dioxide listed in Section 3 does not show an increase in lung cancer in the work force as a result of exposure to TiO₂ dust (note that in this product dust does not occur)according to epidemiology studies. IRAC recently evaluated = Group 2b (possibly carcinogenic to humans). Not listed as a carcinogen by NTP, OSHA, ACGIH.

SECTION 12 Ecological Information

Ecotoxicity: Material expected to have low toxicity to aquatic organisms

Mobility: Material dissolves in water. Under extreme circumstances may contaminate ground water.

Persistence and degradability

Biodegradation: readily biodegradable

Atmospheric oxidation: expected to degrade rapidly in atmosphere

Bioaccumulation potential: extremely low potential to bioaccumulate

SECTION 13 Disposal Considerations

Methods of disposal: This material may be safely incinerated or landfilled in accordance with federal, state, and local environmental control regulations.

Section 14 Transport Information

International transport regulations

This product is not regulated for transport.



Product Name: Dura-Kote WB White Tint Base Epoxy (A)
Revision Date 10/01/13

<i>Regulatory Information</i>	<i>UN number</i>	<i>Proper shipping name</i>	<i>Class</i>	<i>Packing group</i>	<i>Additional information</i>	<i>Marine pollutant</i>
ADR/RID class					none	
IMDG class					none	
IATA class					none	

SECTION 15 Regulatory Information

TSCA (USA - Toxic Substance Control Act)

All components of this product are listed on the U.S. Toxic Substances Control Act Inventory (TSCA Inventory) or are exempted from listing because of low volume or polymer exemption has been granted with 40 CFR 723.50

SARA Title III (USA – Superfund Amendments and Reauthorization Act)

311/312 Hazard categories

Immediate and delayed health

313 Reportable Ingredients:

Ethylene Glycol Monopropyl Ether CAS# 2807-30-9 (<3%)

302 Extremely Hazardous Substances

None

CERCLA (USA – Comprehensive Response Compensation and Liability Act)

None

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Cotrolled Products Regulations. WHMIS Classification : D2B

IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in section 3.

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or otherwise are in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as hazardous are listed in Section 3 unless otherwise indicated.

EINECS (European Inventory of Existing Commercial Chemical Substances)

Components of this product identified by CAS number are listed

SECTION 16 Other Information



Product Name: Dura-Kote WB White Tint Base Epoxy (A)
Revision Date 10/01/13

National Paint and Coating Hazardous Materials Identification System - HMIS (R)

Health hazard rating – 2

Flammability rating – 1

Physical Hazards - 0

Recommended restriction: for use by trained professionals, having read the complete MSDS

Key Legend:

ACGIH – American Conference of Governmental Industrial Hygienists

OSHA – Occupational Safety and Health Administration

NTP – National Toxicology Program

IARC – International Agency for Research on Cancer

R – Risk Phrases

S – Safety Phrases

Date of printing 08/15/12

To the best of our knowledge the information contained here is accurate. However, neither the above named manufacturer nor any of its distributors assumes any liability whatsoever for the accuracy or the completeness of the information contained herein. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.
